

**IN THE CLAIMS:**

1. (Currently Amended) A banknote detecting unit for a banknote distinguishing device comprising:

a housing having a banknote receiving opening to a banknote passageway with a light restrictive projection extending into its banknote passageway adjacent the opening to provide a

5 non-linear portion of the initial banknote passageway to limit the admission of ambient light,

a transportation unit for transporting the banknote through the passageway;

a starting sensor unit positioned adjacent the banknote receiving opening and downstream of the light restrictive projection to sense with radiation an introduction of the banknote;

a first transmission sensor unit including

10 a first light emitting section emitting a first light with a first wavelength, and

a first light receiving section, wherein the first light emitting section and the first light receiving section are located on an optical axis of the first light emitting section which slants relative to [[a]] the banknote passageway, and the first light emitting section and the first light receiving section are positioned on opposite sides of a banknote passageway;

15 a first reflecting sensor unit including

the first light emitting section, and

a second light receiving section, wherein the first light emitting section and the second light receiving section are located on one side of the banknote passageway;

a second transmission sensor unit including

20 a second light emitting section located on an opposing side of the banknote passageway relative to the first light emitting section, the second light emitting section emitting a second light with a second wavelength, and

the second light receiving section located to receive the second light passing through the banknote passageway;

- 25       a second reflection sensor unit including  
          the second light emitting section, and  
          the first light receiving section;

- a microprocessor controlling a switching of the first light emitting section to emit the first light of the first wavelength and a switching of the second light emitting section to emit the  
30   second light of the second wavelength;

- a first emitting amount adjusting unit adjusting an emitting amount of the first light emitting section such that the emitting amount of the first light emitting section reaches a first predetermined emitting amount, wherein the adjustment of the emitting amount of the first light emitting section is performed through detection of the first light by the first light receiving  
35   section;

- a second emitting amount adjusting unit adjusting an emitting amount of the second light emitting section such that the emitting amount of the second light emitting section reaches a second predetermined emitting amount, wherein the adjustment of the emitting amount of the second light emitting section is performed through detection of the second light by the second  
40   light receiving section;

          a first amplifier for the second transmission sensor unit adapted to amplify an output of the second light receiving section at a first predetermined gain;

- a second amplifier for the first reflection sensor unit adjusting a gain of the output of the second light receiving section such that the gain of the output of the second light receiving  
45   section reaches a first predetermined amount defined for the second light receiving section when

a standard paper for adjusting is inserted into the banknote passageway and light is emitted from the first light emitting section;

a third amplifier for the first transmission sensor unit adapted to amplify an output of the first light receiving section at a second predetermined gain; and

50 a fourth amplifier for the second reflection sensor unit adjusting a gain of the output of the first light receiving section such that the gain of the output of the first light receiving section reaches a second predetermined amount defined for the first light receiving section when the standard paper for adjusting is inserted into the banknote passageway and light is emitted from the second light emitting section.

2. (Original) The banknote detecting unit for the banknote distinguishing device claimed in Claim 1 wherein the first optical axis crosses at an obtuse angle relative to the banknote's traveling direction.

3. (Previously Presented) The banknote detecting unit for the banknote distinguishing device claimed in Claim 1 wherein the second light emitting section is located on a second optical axis.

4. (Cancelled)

5. (Previously Presented) The banknote detecting unit for the banknote distinguishing device claimed in Claim 3 wherein the first light emitting section projects infrared light radiation, and the second light emitting section emits non-infrared light radiation.

6. (Previously Presented) The banknote detecting unit for the banknote distinguishing device claimed in Claim 3:

further includes a reading controlling unit which, when the first light emitting section emits rays, a receiving output of the first receiving section is read, and afterwards emitting from the first emitting section stops, when the second light emitting section emits rays, the receiving output of the second light receiving section is read, and afterwards the receiving output of the first light receiving section is read.

7. (Currently Amended) The banknote detecting unit for the banknote distinguishing device comprising:

a housing having a banknote receiving opening to a banknote passageway with a light restrictive projection extending into its banknote passageway adjacent the opening to provide a non-linear portion of the initial banknote passageway to limit the admission of ambient light,

a transportation unit for transporting the banknote through the passageway;

a starting sensor unit positioned adjacent the banknote receiving opening and downstream of the light restrictive projection to sense with radiation an introduction of the banknote;

a first transmitting sensor is structured by a first light emitting section which slants at a first light axis to [[a]] the banknote passageway and a first light receiving section which is located on the first light axis and is located opposite the first light emitting section relative to the banknote passageway,

a first reflecting sensor which is structured by the first light emitting section and a second light receiving section which is located on the same side of the first light emitting section relative to the banknote passageway,

an emitting amount adjusting unit which adjusts an emitting amount, when the first light emitting section emits an output of the first light receiving section at a predetermined amount, and

20 a receiving outputting adjusting unit which adjusts a gain to the output of the second light receiving section when the output reaches a predetermined amount from the second light receiving section, a standard paper for adjusting is inserted into a banknote passageway, and light is emitted from the first light emitting section.

8. (Currently Amended) In a document verification system for receiving and verifying the authenticity of a document adjacent a document passageway, the improvement comprising:

5 a housing having a document receiving opening to the document passageway with a light restrictive projection extending into its document passageway adjacent the opening to provide a non-linear portion of the initial document passageway to limit the admission of ambient light,

a transportation unit for transporting the document through the passageway;

10 a starting sensor unit positioned adjacent the document receiving opening and downstream of the light restrictive projection to sense with radiation an introduction of the document;

a transmitting sensor assembly for emitting radiation to contact a document operatively positioned relative to the document passageway including a first radiation emitting section on one side of the document passageway and a first radiation receiving section on another side of the document passageway, the optical axis of the first radiation emitting section and first  
15 radiation receiving section is slanted relative to an axis of the document passageway;

a first emitting amount adjusting unit adjusting an emitting amount of the first radiation emitting section such that the emitting amount of the first radiation emitting section reaches a first predetermined emitting amount, wherein the adjustment of the emitting amount of the first radiation emitting section is performed through detection of a first radiation amount by the first radiation receiving section;

a reflecting sensor assembly for receiving reflected radiation from the document including a second radiation receiving section positioned on the same side of the document passageway as the first radiation emitting section and operatively positioned to receive reflected radiation after contact with the document wherein the first radiation receiving section receives radiation transmitted through the document; [[and]]

a second emitting amount adjusting unit adjusting an emitting amount of the second radiation emitting section such that the emitting amount of the second radiation emitting section reaches a second predetermined emitting amount, wherein the adjustment of the emitting amount of the second radiation emitting section is performed through detection of a second radiation amount by the second radiation receiving section, and

a document stabilizer unit having an upper stabilizer and a lower stabilizer to provide a narrow document passageway of a configuration to flatten and stretch the document to eliminate creases in the document as the document is transported through the transmitting sensor assembly and the reflecting sensor assembly.

9. (Currently Amended) In a document verification system for receiving and verifying the authenticity of a document adjacent a document passageway, the improvement comprising:

a housing having a document receiving opening to the document passageway with a light  
5 restrictive projection extending into its document passageway adjacent the opening to provide a  
non-linear portion of an initial document passageway to limit the admission of ambient light,

a transportation unit for transporting the document through the passageway;

a starting sensor unit positioned adjacent the document receiving opening and  
downstream of the light restrictive projection to sense with radiation an introduction of the  
10 document;

a first transmitting sensor assembly for emitting radiation to contact a document operatively positioned relative to the document passageway including a first radiation emitting section on a first side of the document passageway and a first radiation receiving section on a second side of the document passageway, a first optical axis of the first radiation emitting section  
15 and first radiation receiving section is slanted relative to an axis of the document passageway;

a first reflecting sensor assembly for receiving reflected radiation from the document including a second radiation reflection receiving section positioned on the first side of the document passageway and operatively positioned to receive reflected radiation after contact with the document wherein the first radiation receiving section receives radiation transmitted through  
20 the document;

a second transmitting sensor assembly for emitting radiation to contact a document operatively positioned relative to the document passageway including a second radiation

emitting section on a second side of the document passageway and a second radiation receiving section on the first side of the document passageway, a second optical axis of the second  
25 radiation emitting section and second radiation receiving section is slanted relative to an axis of the document passageway and crosses the first optical axis;

a second reflecting sensor assembly for receiving reflected radiation from the document including a first radiation reflection receiving section positioned on the second side of the document passageway and operatively positioned to receive reflected radiation after contact with  
30 the document wherein the second radiation receiving section receives radiation transmitted through the document;

a control unit to activate the first radiation emitting section and the second radiation emitting section in a manner to avoid interference between the emitted radiation;

a first amplifier for the second transmitting sensor assembly adapted to amplify an output  
35 of the second radiation receiving section at a first predetermined gain;

a second amplifier for the first reflecting sensor assembly adjusting a gain of the output of the second radiation receiving section such that the gain of the output of the second radiation receiving section reaches a first predetermined amount defined for the second radiation receiving section when a standard paper for adjusting is inserted into the banknote passageway and light is  
40 emitted from the first radiation emitting section;

a third amplifier for the first transmitting sensor unit adapted to amplify an output of the first radiation receiving section at a second predetermined gain; and

a fourth amplifier for the second reflecting sensor unit adjusting a gain of the output of the first radiation receiving section such that the gain of the output of the first radiation receiving  
45 section reaches a second predetermined amount defined for the first radiation receiving section



when the standard paper for adjusting is inserted into the banknote passageway and light is emitted from the second radiation emitting section.

10. (Original) The document verification system of Claim 9 wherein the first radiation emitting section emits light at a first wavelength and the second radiation emitting section emits light at a second wavelength different than the first wavelength.

11. (Original) The document verification system of Claim 9 wherein the control unit activates the first radiation emitting section and the second radiation emitting section multiple times during a transit of a document to provide a set of data representative of the document to be verified.

12. (Original) The document verification system of Claim 11 wherein the control unit stores a predetermined set of data representative of a valid document and compares the set of data representative of the document to be verified and issues a verification signal if the comparison is within predetermined ranges.

13. (Previously Presented) The banknote detecting unit for the banknote distinguishing device claimed in Claim 6 wherein the standard paper is a standard calibrating paper.

14. (Previously Presented) The banknote detecting unit for the banknote distinguishing device claimed in Claim 13 further comprising an initial setting button connected to the microprocessor and sending an initial setting signal to the microprocessor when activated.